


"Control of Plasma Transitions in Sputter Processing
Systems" by Sellers
Serial No.: Not Yet Assigned Filed: Herewith
Atty Docket No.: ASX-064 (473/79)
Jamie H. Rose (617) 248-7376
Sheet 1 of 10



"Control of Plasma Transitions in Sputter Processing
Systems" by Sellers
Serial No.: Not Yet Assigned Filed: Herewith
Atty Docket No.: ASX-064 (473/79)
Jamie H. Rose (617) 248-7376
Sheet 2 of 10




FIG. 1b

"Control of Plasma Transitions in Sputter Processing Systems" by Sellers
 Serial No.: Not Yet Assigned Filed: Herewith
 Atty Docket No.: ASX-064 (473/79)
 Jamie H. Rose (617) 248-7376
 Sheet 3 of 10




FIG. 1c




FIG. 1d

"Control of Plasma Transitions in Sputter Processing Systems" by Sellers
Serial No.: Not Yet Assigned Filed: Herewith
Atty Docket No.: ASX-064 (473/79)
Jamie H. Rose (617) 248-7376
Sheet 5 of 10

300

↓

providing a resonant circuit in electrical communication with an output of a power supply and an input of a plasma vessel
(Step 310)

↓

detecting a change in a signal that indicates a transition of a state of a plasma in the plasma vessel
(Step 320)

↓

shunting the resonant circuit after the change is detected to permit a resonance of the resonant circuit
(Step 330)

↓

waiting for a half cycle before again shunting if the arc discharge plasma persists
(Step 340)

↓

repeating shunting and waiting until the change is no longer detected
(Step 350)

↓

detecting a change in a second signal that indicates the transition of the state of the plasma or reignition of the plasma
(Step 360)

↓

reigniting the plasma after extinguishing the undesired plasma state
(Step 370)

FIG. 3

"Control of Plasma Transitions in Sputter Processing
Systems" by Sellers
Serial No.: Not Yet Assigned Filed: Herewith
Atty Docket No.: ASX-064 (473/79)
Jamie H. Rose (617) 248-7376
Sheet 6 of 10




FIG. 4




FIG. 5

"Control of Plasma Transitions in Sputter Processing
Systems" by Sellers
Serial No.: Not Yet Assigned Filed: Herewith
Atty Docket No.: ASX-064 (473/79)
Jamie H. Rose (617) 248-7376
Sheet 7 of 10




FIG. 6

"Control of Plasma Transitions in Sputter Processing Systems" by Sellers

Serial No.: Not Yet Assigned Filed: Herewith

Atty Docket No.: ASX-064 (473/79)

Jamie H. Rose (617) 248-7376

Sheet 8 of 10




FIG. 7




FIG. 11

"Control of Plasma Transitions in Sputter Processing
Systems" by Sellers
Serial No.: Not Yet Assigned Filed: Herewith
Atty Docket No.: ASX-064 (473/79)
Jamic H. Rose (617) 248-7376
Sheet 9 of 10





FIG. 9

"Control of Plasma Transitions in Sputter Processing Systems" by Sellers
Serial No.: Not Yet Assigned Filed: Herewith
Atty Docket No.: ASX-064 (473/79)
Jamie H. Rose (617) 248-7376
Sheet 10 of 10

1000

↓

providing a resonant circuit in electrical communication with an output of a power supply and an input of a plasma vessel, the resonant circuit for storing and releasing energy
(Step 1010)

↓

shunting the resonant circuit to increase an energy stored in the resonant circuit
(Step 1020)

↓

removing the shunt to direct the stored energy to the input of the plasma vessel to ignite the plasma in the plasma vessel
(Step 1030)

↓

sensing a signal associated with a state of a plasma in the plasma vessel
(Step 1040)

↓

shunting to extinguish a plasma in the plasma vessel if the signal indicates an undesired plasma state of the plasma in the plasma vessel
(Step 1050)

FIG. 10